Application No. 10/679,659 Amendment dated 07/24/2006 Office Action dated 3/22/2006 02-ASD-270 (EM)

Amendments to the Claims:

No changes to claims

Listing of Claims:

- 1. (Previously amended) A method of sealing a gasketed joint comprising:
 - disposing a first gasket having a first edge on a surface of a first member to be sealed;
 - disposing a second gasket having a second edge on said surface adjacent an edge of said first gasket, wherein the first edge and the second edge form a pocket between the first and second gaskets;
 - disposing a measured amount of curable sealant in said pocket;
 - disposing a surface of a second member to be sealed over said first and second gasket;
 - compressing said gaskets to disperse said sealant and fill said pocket; and, curing said sealant to form the gasketed joint between the first and second gaskets.
- (Original) The method defined in claim 1, wherein said step of disposing a measured amount of sealant includes disposing a pellet of uncured elastomer.
- 3. (Original) The method defined in claim 1, wherein said step of disposing includes applying said sealant in semi-liquid form.
- 4. (Original) The method defined in claim 1, wherein said step of disposing curable sealant includes disposing a silicone gel.
- 5. (Original) The method defined in claim 1, wherein said step of curing said sealant includes one of (i) ambient temperature curing, (ii) elevated temperature curing (iii) irradiating.

Application No. 10/679,659 Amendment dated 07/24/2006 Office Action dated 3/22/2006 02-ASD-270 (EM)

- 6. (Previously amended) The method defined in claim 1, wherein the pocket is "V" shaped.
- 7. (Original) The method defined in claim 6, wherein said step of dispersing includes flowing sealant into narrow side channels of said "V" shape.
- 8. (Previously amended) The method defined in claim 1, wherein said step of disposing a first and second gasket includes disposing a gasket of material stiffer in compression than said cured sealant.